

Submitted Model No.: _____

Specific Features: _____



see what Delta can do™

HAND SHOWER

- H2Okinetic® Hand Shower
- Wall Mount or Shower Arm Mount
- Certified Dual Check Valves

STANDARD SPECIFICATIONS:

- Maximum 1.75 gpm @ 80 psi, 6.6 L/min @ 550 kPa
- Hand held shower with one setting
- Adjustable shower arm mount (54421-PK) or wall mount (54421 & 54421-PK) for hands-free showering
- 60"-82" (1524 mm - 2083 mm) metal stretchable hose (54421-PK & 55421)
- Spray face rotates 360°

WARRANTY

- Parts and Finish - Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.
- Electronic Parts and Batteries (if applicable) - 5 years from the date of purchase; or for commercial purchasers, 1 year from the date of purchase. No warranty is provided on batteries.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1 ◆
- ASME A112.18.3
- EPA WaterSense®

<p>54421▲-PK 1.75 GPM</p> <p>H₂Okinetic® PowerDrench® Spray</p>	<p>55421▲ 1.75 GPM</p> <p>H₂Okinetic® PowerDrench® Spray</p>
<p>59421▲-PK 1.75 GPM</p> <p>H₂Okinetic® PowerDrench® Spray</p>	Empty space for diagram

▲ Designate proper finish suffix

◆ Your Delta Faucet handshower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3 and ASME A112.18.1/CSA B125.1. It incorporates two certified check valves in series, which operate independently and are integral, non-serviceable parts of the wand assembly.

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.

DSP-B-54421-PK Rev. B

Delta Faucet Company
 55 E. 111th Street, Indianapolis, IN 46280
 350 South Edgeware Road, St. Thomas, ON N5P 4L1
 © 2018 Delta Faucet Company